

ANTI-SCUFF PASTE STANDARD, 845 & 868

The 3 **Spanjaard Anti-Scuff Pastes** in our range all contain a high percentage of MoS₂.

They are all used for the assembly of moving parts to prevent scuffing and scoring when running in and to provide initial lubrication before an elastohydrodynamic lubricating film can be formed.

In addition, they are used for the pre-treatment of large open gears prior to conversion to Open Gear Lubricant 1279.

The load-carrying capacity of MoS₂ is in excess of 2 750 Mpa (400 000 psi). No fluid lubricants are capable of withstanding such high loads.

The different properties of the 3 **Spanjaard Anti-Scuff Pastes** are highlighted in the table below.



Typical Properties		Standard Grade	845	868
Worked penetration 1/10mm		285	280	295
MoS ₂ particle size		0,7μ Av.	0,7μ Av.	0,7μ Av.
Drop point °C		180	>200	210
Base		Petroleum	Petroleum	Synthetic
Thickener		Lithium	Lithium	Lithium Complex
Applications				
Complies with Lubricant for		-	Mil-M-7866	Mil-M-7866
	: Phosphor-bronze bearings	Yes	Yes	No
	: Assembly of engines & assembly of all moving parts for bedding-in without scuffing or scoring.	Yes	Yes	Jet Turbine / Turbo charger's nuts & bolts
Pre-treatment of				
	: Plain bearings	Yes	Yes	Yes
	: gears	Yes	Yes	Yes
	: piston rings	Yes	Yes	Aircraft
	: cams	Yes	Yes	Yes
	: Lathe centres	Yes	Yes	No
Anti-Seize for				
	: Nuts and bolts	Yes	Yes	Aircraft
	: cocks	Yes	Yes	-
	: screw threads (refrigerants systems)	Yes	Yes	-
	: press fittings	Yes	Yes	Yes
	: turbine studs	Yes	Yes	Aircraft
Operating Temperature Range				
	: Lower, °C	-20	-20	-73
	: Upper, °C	150	200	120
Contents of smallest pack		700 g	500 g	500 g
Bigger pack sizes available on request.				

845

This product is manufactured in compliance with DTD 5617; NATO Code S722 and Joint Services Designation ZX-38

868

This product is specifically used in the assembly of jet turbines using synthetic oils. It is a feature of this product that the base will slowly evaporate above 250°C without oxidising, leaving behind the lubricating film.

Approved as an anti-seize compound on nuts and threads/studs in the higher temperature zone of the ABB turbo chargers.

HANDLING AND STORAGE

Store under cover with lid closed, away from vibrating floor.

PACKAGING

As shown above,
5kg Tin and larger on Request

CP/mg/Anti-Scuff Paste – May 2016

**Certified as an
ISO 9001 Manufacturer
by the SABS**

**Manufacturers & Distributors of
Special Lubricants & Allied Chemical
Products**

SPANJAARD UK LIMITED
2 NEW STREET SQUARE
LONDON
EC4A 3BZ
ENGLAND
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

SPANJAARD LIMITED
PO BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 (0)11 386 7100
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail：long@kunbond.com