

COLD ZINC GALVANISING SPRAY

Spanjaard Cold Zinc Galvanising Spray is used as a protective final coating or primer wherever iron or steel will be exposed to corrosive conditions. The spray-film contains very fine particles of 95% pure zinc and aluminium. The film dries to a flexible, noncracking, non-chipping coating.

APPLICATIONS

- Restoration of galvanized steel roofing.
- Agricultural machinery, air conditioning units, fences.
- Marine equipment, boat hulls, metal floors and roofs.
- Mining equipment, oil rigs and off-shore drilling TYPICAL PROPERTIES structures.
- Railroad equipment, structural steel tanks, transmission towers.
- Underground pipe lines, ducts, automotive bodies.
- Will eliminate atmospheric galvanic corrosion.
- It eliminates corrosion on weld and previously galvanized surfaces.

APPLICATION INSTRUCTIONS

AEROSOL

- 1. Surface to be treated must be totally free of rust, dirt, oil, etc. If necessary, sandblast or clean with sandpaper.
- 2. Shake can vigorously until agitator ball is free and continue shaking thereafter for further 30 seconds.
- 3. Hold can upright; spray \pm 20cm away from surface. At least 4 coats (100µ) should be applied, allowing time for drying before applying next coat.

BULK

- 1. Mix well before use.
- 2. Can be applied by spray gun, brush or roller

SPANJAARD

Colour	Silver
Density, g/ml	1,10
Salt Fog, No rust (@ 4 spray coats =	
100µ) hours	400
Humidity Cabinet, Pass, hours	>1500
Coverage (1 coat / 400g aerosol), m ²	1,35

HANDLING AND STORAGE

Extremely flammable aerosol. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat / sparks / flames / hot surfaces. No Smoking. Do not pierce or burn, even when empty. Do not spray onto an open flame or any incandescent material. 44% by mass of the contents are flammable. Harmful by inhalation and in contact with skin. Causes skin irritation. Causes eye irritation. Vapour may cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Keep out of reach of children.

PACKAGING

400ml aerosol 5L bulk packs

CP/mg/Cold Zinc Galvanising Spray - May 2016

Certified as an ISO 9001 Manufacturer by the SABS

Manufacturers & Distributors of **Special Lubricants & Allied Chemical** Products

SPANJAARD UK LIMITED 2 NEW STREET SQUARE LONDON EC4A 3BZ ENGLAND ENGL @spanjaard.biz WEBSITE:

SPANJAARD LIMITED PO BOX 7294 JOHANNESBURG SOUTH AFRICA TEL: +27 (0)11 386 7100 EMAIL: sales@spaniaard EMAIL: <u>sales@spanjaard.biz</u> WEBSITE: <u>www.spanjaard.biz</u>

中国区销售和技术服务商:上海昆邦化工有限公司

电话:021-58528856 59923197 传真:021-58528166 E-mail:long@kunbond.com