

## EP2 GREASE

Spanjaard EP2 Grease is a high quality, all purpose, and lithium-based grease.

### APPLICATIONS

Suitable for lubrication of plain, needle, ball and roller bearing of all types. **Spanjaard EP2 Grease** is fortified with rust and oxidation inhibitors.

**Spanjaard EP2 Grease** is suitable for lubrication of automotive, industrial equipment and mining equipment.

### APPLICATION INSTRUCTIONS

Apply by hand or grease gun. Compatible with other competitive lithium greases. It is always a good practice to flush out old grease when switching lubricants. This is achieved by frequent re-greasing over a short time span.

It is essential that dust and dirt do not get into the bearings and care must be taken to prevent this during grease storage and packing of bearings.

### HANDLING AND STORAGE

Store under cover with lid closed away from vibrating floor. Remove excess from skin and wash with Spanjaard Hand Cleaner followed by soap and water.

### TYPICAL PROPERTIES

Colour	Beige
Consistency - NLGI grade	2
Worked Penetration, 25°C, 1/10mm	280
Thickener	Lithium Soap
Appearance Texture	Smooth
Drop Point, °C	>180
Dynamic Rust Test	<1
Copper Corrosion - 24hr/100°C	Pass
Oil Separation 18h @ 40°C, %	<2
Water Wash Out @ 38°C, %	<2
@ 79°C, %	<4
Rust Prevention	Pass
Timken OK Load, kg	>27
Operating Temperature	
Continuous service, °C	-20 to 120

### BASE OIL PROPERTIES

Oil Viscosity cSt, 40°C	200
Flash Point, °C	>225



### PACKAGING

400g cartridge; 500g; 5kg; 15kg; 50kg; 180kg.

CP/mg/ EP 2 Grease – Sep 2017

Certified as an  
ISO 9001 Manufacturer  
by the SABS

Manufacturers & Distributors of  
Special Lubricants & Allied Chemical  
Products

SPANJAARD UK LIMITED  
2 NEW STREET SQUARE  
LONDON  
EC4A 3BZ  
ENGLAND  
EMAIL: [sales@spanjaard.biz](mailto:sales@spanjaard.biz)  
WEBSITE: [www.spanjaard.biz](http://www.spanjaard.biz)

SPANJAARD LIMITED  
PO BOX 7294  
JOHANNESBURG  
2000  
SOUTH AFRICA  
TEL: +27 (0)11 386 7100  
EMAIL: [sales@spanjaard.biz](mailto:sales@spanjaard.biz)  
WEBSITE: [www.spanjaard.biz](http://www.spanjaard.biz)

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail: [long@kunbond.com](mailto:long@kunbond.com)