

Data Sheet

EXHAUST & MANIFOLD PAINT

A high temperature, quick drying **Spanjaard Exhaust & Manifold Paint** Spray which is heat resistant up to 650°C. Available in matt-black and silver in an ozone friendly aerosol spray.

APPLICATIONS

A superior matt spray paint in black or silver for vehicle exhausts and manifolds. It can also be used for other applications where this type of finish is required. The paint is quick drying as well as scuff and chip resistant. It will harden completely at room temperature.

APPLICATION INSTRUCTIONS

Surface preparation is very important to ensure a good bonding paint coat. Clean surfaces to be treated with a wire brush to remove any loose deposits e.g. rust and old paint. Completely remove any oil or grease film on the surface to be painted by using lacquer thinners. Apply spray when surface is cold. Hold can upright and spray surface evenly from a distance of 15cm. Further coats can be applied at five minute intervals.

TYPICAL PROPERTIES

 $\begin{array}{ll} \text{Colours} & \text{Black, Silver} \\ \text{Density, g/m}\ell & \text{1,02-1,08} \\ \text{Flammability} & \text{Highly Flammable} \end{array}$

HANDLING AND STORAGE

Highly flammable solvent contents. Use in a well ventilated area. Do not spray near open flame or incandescent material. Pressurised container. Store away from direct sunlight on temperatures above 50 \Box C. Do not puncture or incinerate aerosol can even when empty. Keep out of reach of children. Store under cover.





PACKAGING

300ml (Black) Aerosol 300ml (Silver) Aerosol

CP/mg/Exhaust & Manifold Paint - May 2016

Certified as an ISO 9001 Manufacturer by the SABS

Manufacturers & Distributors of Special Lubricants & Allied Chemical Products SPANJAARD UK LIMITED 2 NEW STREET SQUARE LONDON EC4A 3BZ ENGLAND EMAIL: sales@spanjaard.biz WFRSITE: www.spanjaard.biz SPANJAARD LIMITED PO BOX 7294 JOHANNESBURG 2000 SOUTH AFRICA TEL: +27 (0)11 386 7100 EMAIL: sales@spanjaard.biz WEBSITE: www.spanjaard.biz