



## HT GREASE 777 (WHITE)

Spanjaard HT GREASE 777 (WHITE) is a white NLGI No. 2 consistency lubricant, for use as a long term grease in key applications and also as an assembly and anti-seize compound where cleanliness is of prime importance.

### APPLICATIONS

For grease lubrication of food and bottling machinery, photocopiers, typewriters, and printing machines; vacuum cleaners, washing machines, dishwashers, tumble dryers; adjustable awnings, garage door slides; precision instruments; optical equipment; textile and packaging machinery; fridges and deep freezers; splines and sliding surfaces; anti-seize for all types of bolts, nuts and fasteners.

### APPLICATION INSTRUCTIONS

Apply a coating by brush or chamois. Anti-friction bearings are either prepacked or relubricated by a grease gun.

### ADVANTAGES

Long service life grease with high load carrying capacity due to solid lubricant content. Functions as a highly fortified grease in high load; high temperature conditions. Prevents stick slip; Resists fretting corrosion. Good water resistance. Low co-efficient of friction in threaded connections. Effective to 1200°C in anti-seize applications.

Colour	White
Thickener	Lithium
Operating Temp °C	-20 to 120
Drop Point, °C	250
Mineral oil content, %	85
Oil V.I.	95
Oil viscosity at 100°C, cSt	18
Worked penetration, 25°C, 1/10mm	280
Solid submicron lubricant	white dispersion
EP additive	Additional



### HANDLING AND STORAGE

Minimise skin contact. Store under cover away from vibrating floor. See also safety data sheet.

### PACKAGING

500g Tin; 5kg Tin; 15kg Keg

### TYPICAL PROPERTIES

CP/mg/HT Grease 777 (White) – May 2016