

## LGR- T GEAR OIL

**Spanjaard LGR-T Gear Oil** is a heavy duty ready-for-use blended oil containing Molybdenum Disulphide and other extreme pressure additives.

The product is thixotropic which means that although it is in a gel form when static, it will become a fluid as soon as it is stirred/agitated.

### APPLICATIONS

**Spanjaard LGR-T Gear Oil** was specifically developed for industrial gearboxes where loss of the gear oil due to leaking seals is a problem.

Hand-held power tools such as heavy drills, angle grinders, etc.

Industrial gearboxes operating at excessive temperatures due to high loadings - this application should be established by trial and error. Under certain conditions it may be preferable to add up to 20% by volume of our Spanjaard "G" Gear Oil Supplement to the existing oil - under certain operating conditions a lighter oil may be more appropriate from the point of view of heat dissipation.

### APPLICATION INSTRUCTIONS

**Spanjaard LGR-T Gear Oil** should first be stirred to facilitate pouring.

### TYPICAL PROPERTIES

Consistency-NLGI grade (unstirred)	2 <sup>1</sup> / <sub>2</sub>
Penetration, unworked, 1/10mm	260
Colour	Black
Density, g/cm	0,9
Viscosity spindle no. 6, 20 rpm, @ 25°C, Cps	10500
Oil Viscosity, cSt, 40°C	1100
Weld Load, kg	250
Rust Prevention	Pass
Copper Corrosion	1
Flash Point, COC, °C	255



### HANDLING AND STORAGE

Minimise skin contact. Store under cover. See also Safety Data Sheet.

### PACKAGING

5kg, 15kg & 50kg Steel Containers

CP/mg/LGR-T- June 2016

Certified as an  
ISO 9001 Manufacturer  
by the SABS

Manufacturers & Distributors of  
Special Lubricants & Allied Chemical  
Products

SPANJAARD UK LIMITED  
2 NEW STREET SQUARE  
LONDON  
EC4A 3BZ  
ENGLAND  
EMAIL: [sales@spanjaard.biz](mailto:sales@spanjaard.biz)  
WEBSITE: [www.spanjaard.biz](http://www.spanjaard.biz)

SPANJAARD LIMITED  
PO BOX 7294  
JOHANNESBURG  
2000  
SOUTH AFRICA  
TEL: +27 (0)11 386 7100  
EMAIL: [sales@spanjaard.biz](mailto:sales@spanjaard.biz)  
WEBSITE: [www.spanjaard.biz](http://www.spanjaard.biz)

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail：[long@kunbond.com](mailto:long@kunbond.com)