

MOULD PROTECTOR

Spanjaard Mould Protector is a light coloured, waxy, corrosion protector for moulds, dies and machine tools. The protective film does not need to be removed before re-use. Available in an easy to apply, ozone friendly, aerosol. (A "blue coloured" aerosol and bulk version is also available).

APPLICATIONS

Spanjaard Mould Protector was developed for corrosion protection of steel injection and extrusion moulds in storage between use (e.g. plastic industry).

Displaces and repels water. Protects metal surfaces from rust and acid/alkali attack.

The thin, light coloured, film allows subsequent use of the mould without the necessity of removing the protective film.

Spanjaard Mould Protector will protect all steel and other metal surfaces against corrosion e.g. tools, machinery, parts, weapons, interior voids of cars, etc.

APPLICATION INSTRUCTIONS

Shake aerosol can and spray evenly 20cm from surface. Allow to dry for 30 seconds and apply second coat (coating can be removed with white spirits or aromatic solvent).

TYPICAL PROPERTIES

Density at 20°C	0,845
Appearance	Light Beige
Flammability	Flammable-Cat 2
Humidity Cabinet, 1000hr	Pass
Salt Fog Corrosion, 100hr	Pass

PROTECTION PERIOD AND COATING

Minimum protection of 12 months indoor storage.

400ml aerosol covers $\pm 1\text{m}^2$ (1 coat)

1 litre of bulk covers $\pm 2,5\text{m}^2$ (1 coat)

HANDLING AND STORAGE

Caution: Extremely flammable aerosol. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat / sparks / flames / hot surfaces. No Smoking. Do not pierce or burn, even when empty. Do not spray onto an open flame or any incandescent material. 90% by mass of the contents are flammable. Causes skin irritation. May cause drowsiness or dizziness. Do not breathe vapour. Keep out of reach of children



PACKAGING

400ml aerosol can.

5 litre and 20 litre bulk packs.

(The 400ml aerosol and 5 litre tins is also available in a "blue coloured" version).

CP/mg/Mould Protector – June 2016