



NON-MELT GREASE

Spanjaard Non-Melt Grease is a bentonite grease prepared by a gelling process, no soaps being included. The features obtained are: great stability at high temperatures, resistance to water and acids, and infusibility. It will not soften under heavy working conditions up to its working temperature limit. Protects against wear, oxidation, corrosion and ensures longer life. Minimises fretting corrosion. Prolongs periods between maintenance and routine greasing.

APPLICATIONS

The non-melt properties of **Spanjaard Non-Melt Grease**, together with its Molybdenum Disulphide content, make it particularly suitable for use where high temperature and/or heavy load conditions exist. All medium and large size plain bearings, large diameter ball and roller bearings, running at low r.p.m. For mechanical equipment, particularly when exposed to severe weather conditions or subjected to extreme loads i.e. cranes - conveyor systems - ore crushers - rolling mills - mechanical stokers - printing presses - drilling rigs and ancillary equipment - exposed drives and locomotives - dock equipment - cargo and warping winches - lifeboat davits - hatch covers - ships stabilizers. Springs - shackle bolts - king pins - torsion bar bushings - water pumps - brake linings on all types of transport and mobile equipment.

Compatibility: **Spanjaard Non-Melt Grease** is incompatible with most other grease thickener systems. This is true for all Bentone, non-soap thickened greases which are prepared by a gelling process.

The gelling process stability can be affected by the anti-rust and extreme pressure additives of other greases that are still in the bearing. It is therefore very important that any old greases are removed in order to ensure the stability of **Spanjaard Non-Melt Grease**.

TYPICAL PROPERTIES

Colour	Grey/Black
Base	Lubricating Oil
Thickener	Bentonite

Operating Temperature	
Continuous Service, °C	-20 to 160
Short Period Peaks, °C	200
Drop Point	No Drop Point
Consistency	NLGI No. 2
Worked Penetration	265-295
Water Resistance	Excellent
Texture	Smooth Homogeneous Paste
Additives	EP, Anti-oxidant & corrosion inhibitors
Corrosion Stability	Excellent



APPLICATION INSTRUCTIONS

- By hand or grease gun/pump
- Centralised lubricator
- Lubricant applicator or scraper

HANDLING AND STORAGE

Store indoors with lid closed. Keep out of reach of children.

PACKAGING

100g tubes

CP/mg/Non-Melt Grease – July 2017

Certified as an
ISO 9001 Manufacturer
by the SABS

Manufacturers & Distributors of
Special Lubricants & Allied Chemical
Products

SPANJAARD UK LIMITED
2 NEW STREET SQUARE
LONDON
EC4A 3BZ
ENGLAND
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

SPANJAARD LIMITED
PO BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 (0)11 386 7100
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail：long@kunbond.com