

OPEN GEAR LUBRICANT (STANDARD)

Spanjaard Open Gear Lubricant (Std) is a black, tacky, heavy duty, bentone-based lubricant containing oxidation, corrosion, molybdenum disulphide and other extreme pressure additives.

APPLICATIONS

Spanjaard Open Gear Lubricant (Std) is a lower-cost open gear lubricant for all medium to fast-moving open or exposed gears, as found on cranes, excavating plant and winches, suitable for adverse weather conditions or in a contaminated atmosphere e.g. cement works, paper mills, steel mills, drilling rig jacking legs, at sea etc.

TYPICAL PROPERTIES

Colour	Black
Consistency - NLGI Grade	2
Worked penetration, 1/10mm	265-295
Flash Point COC, °C	285
Drop Point	None
Thickener	Bentonite
Base on viscosity	
cSt @ 40°C	550
cSt @ 100°C	36
Operating temperature	
Continuous service, °C	-20 to 160
Short period peaks, °C	200



HANDLING AND STORAGE

Store under cover with lid closed.
Keep out of reach of children.
If swallowed, seek medical help. Do not induce vomiting.

PACKAGING

500g, 5kg, 15kg, 50kg, 180kg

CP/mg/ Open Gear Lubricant(Standard) – July 2016

Certified as an
ISO 9001 Manufacturer
by the SABS

Manufacturers & Distributors of
Special Lubricants & Allied Chemical
Products

SPANJAARD UK LIMITED
2 NEW STREET SQUARE
LONDON
EC4A 3BZ
ENGLAND
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

SPANJAARD LIMITED
PO BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 (0)11 386 7100
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail：long@kunbond.com