

## OPEN GEAR LUBRICANT 1620

**Spanjaard Open Gear Lubricant 1620** is a black adhesive, bituminous lubricant plus non-flammable solvent, which is applied to large open gears, wire ropes or chains in the mining industrial and marine environment. In addition to Molybdenum Disulphide and other solid lubricants **Spanjaard Open Gear Lubricant 1620** contains extreme pressure, anti-fretting and anti-corrosion additives.

### APPLICATIONS

- Excellent for large open gears, wire ropes or chains in mining and construction machinery, crushes, pulverises, ball mills, rod mills, kilns, power shovels, gold and coal mine tippers and similar equipment.
- **Spanjaard Open Gear Lubricant 1620** penetrates to the wire rope core and lubricates and protects wire rope strands in marine and land applications.
- Lubricates cams and shafts.

### APPLICATION INSTRUCTIONS

- By brush.
- Centralised lubricator.
- Wire Rope lubricant applicator/scrapper.
- Spray application. Can be diluted with solvents as required.

### TYPICAL PROPERTIES

Colour	Black
Density, g/ml	1,04
Consistency	Semi-Fluid
Viscosity, 20°C, cps (solvent diluted)	200
Timken OK load, kg	31

### HANDLING AND STORAGE

Store under cover. Do not leave container open, as solvents will evaporate. Minimise skin contact and inhalation of solvent vapours.

### PACKAGING

- 5kg Tin
- 15kg Keg
- 50kg Drum
- 180kg Drum



CP/mg/Open Gear Lubricant 1620 – July 2016