



RADIATOR FLUSH

Spanjaard Radiator Flush is a highly concentrated composition of inorganic ingredients in water, giving powerful dissolving and chelating properties in order to remove scale and rust from the cooling system.

APPLICATIONS

Dissolves and chelates rust, scale and sludge deposits. Helps prevent corrosion. Not harmful to hoses and gaskets. Safe on aluminium blocks.

APPLICATION INSTRUCTIONS

1. Drain off 375ml from radiator.
2. Add entire contents (375ml per \pm 5 litres capacity) to radiator and run engine till water is warm.
3. Keep engine running for further 15 minutes.
4. Flush radiator twice and fill up with fresh water.
5. For on-going protection, fill with Spanjaard Radiator Sealer & Conditioner and Antifreeze/Coolant.



PACKAGING

375ml bottle
5 litre
25 litre

TYPICAL PROPERTIES

Colour	Light yellow
Density, g/ml	1,16

HANDLING AND STORAGE

CAUTION: Causes serious eye damage. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Keep out of reach of children.

CP/mg/Radiator Flush – July 2016

Certified as an
ISO 9001 Manufacturer
by the SABS

Manufacturers & Distributors of
Special Lubricants & Allied Chemical
Products

SPANJAARD UK LIMITED
2 NEW STREET SQUARE
LONDON
EC4A 3BZ
ENGLAND
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

SPANJAARD LIMITED
PO BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 (0)11 386 7100
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz