

RB2-X GREASE

Spanjaard RB2-X Grease is a black, high quality lithium complex grease containing special extreme pressure additives, rust and oxidation inhibitors as well as molybdenum disulphide. **Spanjaard RB2-X Grease** can be widely used in anti-friction bearings or applications subject to slow or high speed, heavy loads and wet conditions.

APPLICATIONS

Spanjaard RB2-X Grease is the heavy-duty service version of RB2 Grease containing extra MoS₂ for high load/shock conditions.

Spanjaard RB2-X Grease can be used for lubrication of slow and high speed ball or roller type bearings and bushes e.g. wheel bearings of all types of motor vehicles, roller and taper bearings of larger transport vehicles, chassis lubrication, universal joints, industrial bearings (electrical motor bearings) and bushes.

Spanjaard RB2-X Grease is well suited for extra heavy duty mining and construction vehicles, particularly those that operate in dusty or wet conditions.

The solid film lubrication formed by molybdenum disulphide provides enhanced lubrication under extremely severe operating conditions. The use of **Spanjaard RB2-X Grease** allows rationalisation of grades thus reducing inventory costs.

APPLICATION INSTRUCTIONS

Apply by hand or grease gun. Compatible with other competitive lithium and lithium complex greases. It is always a good practice to flush out old grease when switching lubricants. This is achieved by frequent re-greasing over a short time span.

It is essential that dust and dirt do not get into the bearings and care must be taken to prevent this during grease storage and packing of bearings.

HANDLING AND STORAGE

Store under cover with lid closed. Do not swallow. If swallowed, seek medical attention

TYPICAL PROPERTIES

Consistency - NLGI grade	2
Worked Penetration, 25°C, 1/10 mm	285
Colour	Black
Thickener	Lithium Complex Soap
Drop Point, °C	>230
Copper Corrosion - 24hr/100°C	Pass
Stability At Low Temperatures	Pass
Timken OK Load, kg	27
Operating Temperature	
Continuous service, °C	-25 to 150

BASE OIL PROPERTIES

Oil Viscosity cSt, 40°C	210
-------------------------	-----

PACKAGING

500 g; 5kg; 15kg; 50kg; 180kg.



CP/mb/ RB2X Grease – Jan 2018

Certified as an
ISO 9001 Manufacturer
by the SABS

Manufacturers & Distributors of
Special Lubricants & Allied Chemical
Products

SPANJAARD UK LIMITED
2 NEW STREET SQUARE
LONDON
EC4A 3BZ
ENGLAND
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

SPANJAARD LIMITED
PO BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 (0)11 386 7100
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail：long@kunbond.com