

SMOKE DOCTOR

An oil additive which prevents wear and improves viscosity at high temperatures. Reduces oil consumption and exhaust smoke in worn engines.

AUTOMOTIVE APPLICATIONS

- improves lubrication
- reduces oil consumption and exhaust smoke in worn motors
- increases engine compression
- reduces wear
- cushions regular impact areas such as tappets, cams and gears
- keeps seals elastic

APPLICATION INSTRUCTIONS

For Engines:

Change oil if required. Run the engine until it reaches operating temperature, then add a full bottle of **Spanjaard Smoke Doctor**.

TYPICAL PROPERTIES

Density at 20°C, g/cm ³	0,89
Viscosity at 100°C, cSt	1300
Colour	Light brown
Flash point °C, C O C	220
Pour point °C	-6
Neutralisation Number D974	1,4



HANDLING AND STORAGE

Store under cover. Keep out of reach of children.

PACKAGING

500ml bottle.

CP/mb/ Smoke Doctor – June 2016

Certified as an
ISO 9001 Manufacturer
by the **SABS**

**Manufacturers & Distributors of
Special Lubricants & Allied Chemical
Products**

SPANJAARD UK LIMITED
2 NEW STREET SQUARE
LONDON
EC4A 3BZ
ENGLAND
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

SPANJAARD LIMITED
PO BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 (0)11 386 7100
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz