

## START-UP

Instant starting aid with upper cylinder lubricant for all engines when starting is a problem in cold and damp weather. Contains upper cylinder lubricant.

### APPLICATIONS

At low temperatures fuel might not vaporise sufficiently giving starting problems.

**Spanjaard Start-Up** is specially formulated to vaporise in cold and damp conditions, giving first time starting.

**Spanjaard Start-Up** can be used for starting all petrol, diesel and paraffin engines in cold and damp weather.

### REPEATED STARTING ATTEMPTS GIVE

- Starter motor wear and battery discharge.
- Cylinder flooding and thus reduced chance of starting.
- Oil film wash away by the fuel.
- Fuel dilution of the crankcase oil.

**Spanjaard Start-Up** contains high vapour pressure hydrocarbons to give instant starting and dispersants to deal with any condensed water.

A special upper cylinder lubricant is also included to reduce wear before oil circulation begins.

A special inhibitor gives controlled burning of fuel instead of explosive and damaging pinking.

### APPLICATION INSTRUCTIONS

**Spanjaard Start-Up** can be used on all petrol, diesel and paraffin engines, e.g. trucks, buses, tractors, earth-moving equipment, stationary engines, cars, outboard motors, lawnmowers, locomotives, 2-stroke engines, etc.

**Petrol Engines** - Do not choke or flood carburettor. Spray directly into air-intake for 2-3 seconds while ignition is off and engine is stationary. Start in normal manner.

**Diesel and Paraffin Engines** - Check fuel filter for wax blockage that might have crystallized out of the fuel due to sudden cold temperature.

Do not use heater plugs. Spray directly into air-intake for 2-3 seconds. Start engine in normal manner.

### HANDLING AND STORAGE

**CAUTION:** Highly flammable. Pressurised aerosol container. Keep away from open flames and heat. Use in well ventilated areas. Protect can from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Keep out of reach of children.



### PACKAGING

350ml/230g aerosol can.

CP/mb/Start Up – June 2016

Certified as an  
ISO 9001 Manufacturer  
by the SABS

Manufacturers & Distributors of  
Special Lubricants & Allied Chemical  
Products

SPANJAARD UK LIMITED  
2 NEW STREET SQUARE  
LONDON  
EC4A 3BZ  
ENGLAND  
EMAIL: [sales@spanjaard.biz](mailto:sales@spanjaard.biz)  
WEBSITE: [www.spanjaard.biz](http://www.spanjaard.biz)

SPANJAARD LIMITED  
PO BOX 7294  
JOHANNESBURG  
2000  
SOUTH AFRICA  
TEL: +27 (0)11 386 7100  
EMAIL: [sales@spanjaard.biz](mailto:sales@spanjaard.biz)  
WEBSITE: [www.spanjaard.biz](http://www.spanjaard.biz)