

SYNTHETIC ULTRA OIL TREATMENT

An extreme pressure oil additive for use in synthetic oils to improve the viscosity at high temperatures and to reduce wear.

Can be mixed with mineral oil based products.

AUTOMOTIVE APPLICATIONS:

- Provides superior lubrication
- reduces oil consumption and exhaust smoke in worn engines
- improves fuel consumption
- increases engine compression
- reduces wear
- Superior cushioning of regular impact areas such as tappets, cams and gears

Spanjaard Synthetic Ultra Oil Treatment added to automatic gearboxes and differentials:

- attains maximum friction reduction without causing the clutches to slip
- reduces wear
- improves viscosity/temperature relationship of the oil for increased periods of service
- will not impair performance of limited-slip differentials.

INDUSTRIAL APPLICATIONS

Eliminates hydraulic shudder when hydraulic oils overheat. Mixing proportions are higher in hot climates and lower in cold climates.

INSTRUCTIONS

FOR ENGINES:

Change oil if required. Run the engine until it reaches operating temperature, then add a full can of Spanjaard Synthetic Ultra Oil Treatment.

FOR AUTOMATIC GEARBOXES AND DIFFERENTIALS:

Add half a can to each.

TYPICAL PROPERTIES

| | |
|------------------------------------|------|
| Density at 20°C, g/cm ³ | 0,88 |
| Viscosity at 40°C, cSt | 220 |
| Colour | blue |
| Flash Point °C, C.O.C. | 160 |
| Pour point °C | -6 |
| Neutralisation Number D974 | 0,5 |
| Timken O K Load D2782, kg | 18 |
| Copper Corrosion D130 | Pass |
| Weld load D2783, Kgf | 500 |
| Wear Scar Diam D4172, mm | 0,73 |



HANDLING AND STORAGE

Keep out of reach of children.

PACKAGING

250ml tin

Certified as an
ISO 9001 Manufacturer
by the SABS

Manufacturers & Distributors of
Special Lubricants & Allied Chemical
Products

SPANJAARD UK LIMITED
2 NEW STREET SQUARE
LONDON
EC4A 3BZ
ENGLAND
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

SPANJAARD LIMITED
PO BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 (0)11 386 7100
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail：long@kunbond.com

CP/mb/ Synthetic Ultra Oil Treatment – June 2016

