



## TOOL JOINT LUBRICANT

**Spanjaard Tool Joint Lubricant** is a non-melt, extreme pressure thread lubricant containing high percentages of graphite and molybdenum disulphide.

### APPLICATIONS

**Spanjaard Tool Joint Lubricant** was specifically designed as a thread lubricant for drill rods, other threads and joints to prevent seizing and galling and to facilitate “breakout” of the drill rods after drilling is completed.

The product acts as a sealant allowing no gas or product seepage along the threads.

The main application is on threads in “slim-hole” drilling in quarries, dam construction, surface mining operations and all types of civil construction projects.

The drill rods are usually 3 or 6 metres long and have a course “rope type” thread commonly used with Ingersoll-Rand and Atlas-Copco equipment.

### APPLICATION INSTRUCTIONS

**Spanjaard Tool Joint Lubricant** is applied to threads by finger or brush.

### TYPICAL PROPERTIES

Colour	Dark Grey
Consistency - NLGI Grade	3
Worked Penetration X60, 1/10mm	230
Solid Lubricants	Yes

### HANDLING AND STORAGE

Store under cover with lid closed away from vibrating floor. Remove excess from skin and wash with Spanjaard Hand Cleaner followed by soap and water.



### PACKAGING

5kg, 15kg, 50kg, 180kg

CP/su/ ToolJntLub – October2013

**Certified as an  
ISO 9001 Manufacturer  
by the SABS**

**Manufacturers &  
Distributors of Specialised  
Lubricants & Allied  
Chemical Products**

P.O. BOX 21  
HUNTINGDON  
CAMBS PE29 2ED  
ENGLAND  
TEL: +44 1480 45-7022  
FAX: +44 1480 45-7022  
WEBSITE: [www.spanjaard.biz](http://www.spanjaard.biz)

P.O. BOX 7294  
JOHANNESBURG  
2000  
SOUTH AFRICA  
TEL: +27 11 386-7100  
FAX: +27 11 786-5685  
EMAIL: [sales@spanjaard.biz](mailto:sales@spanjaard.biz)

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail：[long@kunbond.com](mailto:long@kunbond.com)