



UG2 GREASE

Spanjaard UG2 Grease is a premium polyuria thickened, multipurpose grease specifically designed for use in high speed bearings operating at high temperatures. Excellent long-life properties

APPLICATIONS

The excellent mechanical and thermal stability of **Spanjaard UG2 Grease** makes it suitable for electric motor fan bearings of power stations, wheel bearings, electric motor bearings, generators, pump shaft bearings, conveyor bearings, sleeve bearings, etc.

Excellent under severe water washing, acid contamination and steam exposure where it protects against rusting such as when a plant is seasonally inoperative under humid conditions.

Spanjaard UG2 Grease is compatible with most plastics (ABS, GPPS, HIPS, Nylon, Polyacetal, PB and PC, etc). **Spanjaard UG2 Grease** is used in the lubrication of plastic extrusion equipment where high temperatures are reached for short lubrication intervals. The high viscosity base oil and additives provide excellent high pressure and anti-corrosive film strength to protect against shock loads.

Anti-wear additives protect against metal-to-metal contact giving longer machine life and greater productivity. The grease allows for extended re-lubrication intervals.

The normal operating temperature is -18°C to 180°C and the product conforms to DIN 51502: K2R-20.

APPLICATION INSTRUCTIONS

Apply by hand or grease gun. No compatibility problems have been experienced with aluminium, calcium or urea thickened food grade greases. It is always a good practice to flush out old greases when switching lubricants. This is achieved by frequent re-greasing over a short time span.

TYPICAL PROPERTIES

NLGI Consistency		2
Worked Penetration, 25°C. $\frac{1}{10}$ mm		285
Colour		Blue-green
Thickener		Polyurea
Drop Point, °C		>250
Rust Test, D1743 (3% Synth Sea Water)		Pass
Base Oil Viscosity at	40°C,cSt	110
Operating range, °C		-20 to 180



HANDLING AND STORAGE

Store under cover with lid closed. Remove excess from skin and wash with Spanjaard Hand Cleaner.

PACKAGING

5kg; 15kg; 50kg; 180kg.

CP/mb/ UG2 Grease – June2016

Certified as an
ISO 9001 Manufacturer
by the SABS

Manufacturers & Distributors of
Special Lubricants & Allied Chemical
Products

SPANJAARD UK LIMITED
2 NEW STREET SQUARE
LONDON
EC4A 3BZ
ENGLAND
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

SPANJAARD LIMITED
PO BOX 7294
JOHANNESBURG
2000
SOUTH AFRICA
TEL: +27 (0)11 386 7100
EMAIL: sales@spanjaard.biz
WEBSITE: www.spanjaard.biz

中国区销售和技术服务商：上海昆邦化工有限公司

电话：021-58528856 59923197 传真：021-58528166 E-mail：long@kunbond.com